



oorphones με κορυφαία ποιότητα κατασκευής
θος "έξυπνων" δυνατοτήτων, άμεσα διαθέσιμα!



R23P

Video SIP Doorphone with one Button (Audio)

- *Body material: all-aluminum*
- *Water-proof & Dust-proof: IP65*
- *Output Relay: 2 output relays for door opener*
- *10/100 Mbps Ethernet connection*
- *Voice Activation Detection*
- *Vandal resistant body, with a flush button*
- *PoE (IEEE802.3af, Power-over-Ethernet)*
- *Two-way audio communication over IP networks*
- *Echo Cancelation*
- *Complies with SIP standard for easy integration in every SIP capable PBXes*



R26P

Video SIP Doorphone with one Button (Video)

- *Body material: all-aluminum*
- *Water-proof & Dust-proof: IP65*
- *Output Relay: 2 output relays for door opener*
- *10/100 Mbps Ethernet connection*
- *Camera: 3M pixels, automatic lighting, Resolution: up to 1080p*
- *Max image transfer rate: 1080p - 30fps*
- *Auto-night mode with LED illumination*
- *Compatible to 3rdPartyVideo components, e.g. NVRs*
- *Voice Activation Detection*
- *Vandal resistant body, with a flush button*
- *PoE (IEEE802.3af, Power-over-Ethernet)*
- *Two-way audio communication over IP networks*
- *Echo Cancelation*
- *Complies with SIP standard for easy integration in every SIP capable PBXes*



SDP-R29

Smart IP Android Video Doorphone with card reader.

- Body material: all-aluminum
- Water-proof & Dust-proof: IP65
- Collision-proof: IK06
- Output Relay: 2 output relays for door opener
- Display: 7" IPS LCD
- Screen: 7" capacitive touch screen
- Camera: 5 Mega pixels, automatic lighting
- 10/100 Mbps Ethernet connection
- DHCP Client or Static IP
- Echo Cancellation
- Voice Activation Detection
- Resolution: up to 1080p
- Max image transfer rate: 1080p - 30fps
- Android OS for any 3rd party software or customization
- Auto-night mode with LED illumination
- G-sensor for self-defence alarm
- Multi-way Unlock: IC Card, PassNumber, Gestures



IT81

Indoor monitor for audio and video communication with Door phones via SIP 2.0 protocol.

- 7" capacitive touch screen with energy saving mode
- Reception of a HD picture from the door communicator
- Powered by PoE or external source
- Resolution: 800x480
- Illumination: Edgelit LED
- Touch Screen: Projected Capacitive
- RAM: 64MB, Flash: 128MB
- 2x10/100 Mbps ports
- Built-in microphone and speaker
- Two-way communication with other units in the network, based on SIP v2.0 protocol
- 5 capacitive pushbuttons, programmable, pre-labeled with icons for "SOS", "Contact List", "Unlock", "D

