

Give your guests the freedom to roam, the cordless accessory handset features 3 speed dials and a USB charging port on the charging cradle. Guests will appreciate the cordless freedom, while the hotels will welcome speed dials right on the handset for easy communication. Since this accessory phone registers to a cordless base, there's no need to run an Ethernet cable or purchase a SIP license for installation. The result: lower infrastructure costs and a better guest experience.

Contemporary SIP Cordless Accessory Handset

1-Line CTM-S241SDU | 2-Line CTM-S242SDU

Key Features

- DECT 6.0 technology delivers superior sound quality while reducing telecom costs
- · Cordless handset speakerphone
- Three non-removable, programmable speed dials on handset
- · Antibacterial plastic tested to inhibit 99.9% of bacteria growth
- USB charging port makes it easy for guests to charge smart phones and other electronic devices







Phone Features

- CTM-S241SDU requires base phone: CTM-S2411
- CTM-S242SDU requires base phone: CTM-S2421
- Handset Battery life: up to 7 hours of talk time with 7 days of standby time
- Charge LED feature ensures handset battery is charging
- Low battery indicator on cordless handset for easy maintenance
- Visual message waiting indicator alerts guests of new messages. Compatible with all major PBXs
- Answer a call by simply picking up the handset
- One non-removable, programmable message retrieval speed dial on handset

- Two non-removable, programmable speed dials on handset
- · Conference*, Flash, Hold and Mute
- 1 or 2 lines with line key indication*
- · Automatic line selection*
- Backlit handset dialpad
- Redial the last number called with the touch of a button; automatically expires in 15 minutes to protect guest privacy
- Multi-step volume control for ring tones and handset
- · Side handset volume control for easy access
- 2-year limited warranty
- * 2-line model only



Matte Black





Silver and Pearl













Contemporary SIP Cordless Accessory Handset

1-Line CTM-S241SDU | 2-Line CTM-S242SDU

Specifications

Radio Frequency Baseband: Available in DECT 1.8GHz, and DECT 1.9GHz

Colors: Silver and Black, Matte Black, Silver and Pearl

Power Source: 6V DC External Power

Message Waiting Signal Type: Varies by PBX

Flash: Programmable timing (100/300/600ms)

Humidity: $65\% \pm 20\%$ Temperature: 25° C ± 10° C

Certifications:

- HAC
- FCC Part 15 Class B
- FCC Part 68
- IC
- CE
- ETL
- RoHS
- ENERGY STAR® qualified







Dimensions

Master Carton Measurements: 16.4 in. x 16.3 in. x 9.9 in., 22.3 lbs, 12 per carton Phone Measurements: 1.9 in. x 8.4 in. x 1.7 in.,1.0 lbs



Matte Black





Silver and Pearl





ENERGY STAR and the ENERGY STAR mark are registered trademarks of the U.S. government.



Contemporary SIP Cordless Accessory Handset

1-Line CTM-S241SDU | 2-Line CTM-S242SDU

Product Part Numbers

Handset with speed dials

	Silver and Black	Matte Black	Silver and Pearl
• Model No. CTM-S241SDU:	80-H0CF-06-000	80-H0CF-15-000	80-H0CF-11-000
1-Line Accessory Petite			
Cordless Handset with			
speed dials			
• Model No. CTM-S242SDU:	80-H0CG-06-000	80-H0CG-15-000	80-H0CG-11-000
2-Line Accessory Cordless			





Silver and Black





Matte Black





Silver and Pearl

