

## DNAKE IPK02



### Instruction

Embrace security with a simple touch. DNAKE IP Video Intercom kit is a complete solution that includes a door station, an indoor monitor, and accessories to mount. The new IP intercom kit is immediately ready for use and does not require any special programming. Improve your safety at home while increasing convenience with DNAKE IP Video Intercom Kit!

### Key Features

- Plug & Play
- User friendly interface
- Standard PoE
- One-touch calling
- Remote unlocking and support PIN Code
- CCTV integration

### Package Features

- |                              |                                   |
|------------------------------|-----------------------------------|
| • Package Content:           | • Qty/CTN: 9 pcs                  |
| - DNAKE IPK02                | • N.W/PCS: 1.25 kg                |
| (Power adapter not included) | • G.W/CTN: 14.55 kg               |
| - Bracket                    | • Giftbox Size: 280 x 235 x 65 mm |
| - Screwing Kit               | • Carton Size: 660 x 330 x 280 mm |
| - User Manual                |                                   |



## Key Features

- Easy configuration
- 7-inch capacitive touch screen
- Powered by PoE or power adapter (DC12V/2A)
- Support SIP 2.0 protocol, easy integration with other SIP devices
- Easy integration with elevator control system
- Support monitoring 8 IP cameras

## Physical

- System: Linux
- RAM: 64 MB
- ROM: 128 MB
- Front Panel: Plastic
- Power Supply: PoE (802.3af) or DC 12V/2A
- Standby Power: 1.5 W
- Rated Power: 9 W
- Ethernet Port: 1 x RJ45, 10/100 Mbps adaptive
- RS485: 1
- Power Output: 1 (12V/100mA)
- Doorbell Input: 8 (use any alarm input port)
- Alarm Input: 8
- Installation: Surface Mounting / Desktop
- Dimension: 195 x 130 x 14.5mm
- Working Temperature: -10°C to +55°C
- Storage Temperature: -40°C to +70°C
- Working Humidity: 10% to 90% (non-condensing)

## DNAKE E216



## Display

- Display: 7-inch TFT LCD
- Screen: Capacitive touch screen
- Resolution: 1024 x 600

## Audio

- Audio Codec: G.711
- Echo Cancellation
- DTMF: RFC2833
- Microphone: Built-in microphone
- Speaker: 8Ω / 1W

## Video

- Video Codec: H.264

## Networking

- Protocol: SIP, UDP, TCP, RTP, RTSP, NTP, DNS, HTTP, DHCP, IPV4, ARP, ICMP



## Key Features

- Powered by PoE or power adapter (DC12V/2A)
- Support IC (13.56MHz) & ID (125kHz) card, PIN code
- 3 Indicator Lights
- 2 relays supported
- Tamper alarm
- Keypad supported

## Physical

- System: Linux
- RAM: 64 MB
- ROM: 128 MB
- Front Panel: Aluminum
- Power Supply: PoE (802.3af) or DC 12V/2A
- Standby Power: 1.5 W
- Rated Power: 3.5 W
- Camera: 2MP, CMOS
- Indicator Light: 3
- Wiegand Port: Support
- Ethernet Port: 1 x RJ45, 10/100 Mbps adaptive
- Door Entry: IC (13.56MHz) & ID (125kHz) card, PIN code
- Reset Button: 1
- RS485 Port: 1
- Relay Out: 2
- Input: 2
- IP / IK Rating: IP65 / IK07
- Installation: Surface Mounting
- Surface Mounting DIM: 188 x 88 x 34 mm
- Working Temperature: -40°C to +55°C

## DNAKE S213K (Surface Mounting)



- Storage Temperature: -40°C to +70°C
- Working Humidity: 10% to 90% (non-condensing)

## Audio

- Audio Codec: G.711
- Echo Cancellation
- DTMF: RFC2833
- Microphone: Built-in microphone
- Speaker: Built-in speaker

## Video

- Video Codec: H.264
- Video Resolution: 1280 x 720
- Viewing Angle: 110° (H) / 60° (V) / 125° (D)
- Max. Image Transfer Rate: 720p – 25fps
- Light Compensation: LED white light

## Networking

- Protocol: ONVIF, SIP, UDP, TCP, RTP, RTSP, NTP, DNS, HTTP, DHCP, IPV4, ARP, ICMP

