

MB-Remote

Remote Controller

The Remote Controller is an efficient tool designed by Yealink specifically for pairing with Yealink conference endpoints, aiming to enhance conference efficiency and optimize the conference experience. The Remote Controller has multimedia page-turning, air mouse, and basic meeting control functions, enabling users to better control the conference process and more efficiently convey core points.

Key Features and Benefits

- Plug-and-play
- Collaboration Control
- Convenient Presentation

Plug-and-Play

The Remote Controller uses a USB receiver to connect to the host, ensuring a stable connection within a range of 10 meters through a dedicated 2.4GHz private protocol, realizing 360° no dead angle operation. The Remote Controller is compatible with the Yealink conference endpoint, without the need for cumbersome software installation, plug the receiver into the USB port to start an efficient presentation immediately.

For support status across different terminals, refer to the compatibility list below.

Collaboration Control

Remote Controller provides one-button operation functions, including quickly turning the camera on or off, instant muting of the microphone, and volume adjustment. The operation is simple and can significantly improve the efficiency of the conference.

Convenient Presentation

The Remote Controller is equipped with page up/down buttons and a presentation button, supporting page-turning of documents, presentation files, web pages, etc., and supporting simple presentation operations with a simulated mouse. Its button layout conforms to the grip posture to ensure you can easily and accurately locate the buttons through touch during the presentation process.

Specifications

Technical Specifications	Description
Physical Specifications	<ul style="list-style-type: none"> - Size (L * W * H): <ul style="list-style-type: none"> · With receiver: 144 mm x 30 mm x 16 mm · Without receiver: 134 mm x 30 mm x 16 mm - Weight (including battery, excluding receiver): 51.5 g - Receiver Size: (L * W * H): 34 mm x 15 mm x 7.5 mm - Receiver Weight: 2.5 g

Basic Specifications	<ul style="list-style-type: none"> - Power Consumption (Standby): 0.033 mW - Button: <ul style="list-style-type: none"> · Microphone Mute Button · Volume+ · Volume- · Camera Control Key · Page Up Key · Page Down Key · Presentation Key - Indicator: One (used to indicate low power and pairing)
Battery	<ul style="list-style-type: none"> - Battery Type: 2 AAA batteries - Battery Life: <ul style="list-style-type: none"> - Satisfy 2 hours of use every day for three months(*varies depending on usage)
Connection	<ul style="list-style-type: none"> - Connection Type: 2.4 GHz wireless connection - Connection Range: 10 m
Operating Temperature	0-40°C
Operating Humidity	10-95%

Key Function Compatibility List

Device	Version	Compatibility
Endpoint	MeetingBoard 65/86:155.15.0.62 and later	<ul style="list-style-type: none"> - H.323/SIP: Fully supported - BYOD/General Mode: Camera control keys not supported - Teams: Camera control keys not supported - Zoom: Camera control keys not supported
PC	<ul style="list-style-type: none"> - Windows 10 and later - MacOS 12 and later 	Microphone mute key and camera control keys not supported