

Mechanical

Dimensions	203 x 76 x 33 mm (8 x 3 x 1.3")
Weight	Device: 320 g (11.3 oz) Wall mount: 45 g (1.6 oz) 60W adapter: 330 g (11.6 oz)
Enclosure material	Polycarbonate

Hardware

Management Interface	Ethernet In-Band
Networking Interface	(8) GbE RJ45 ports
PoE Interface	(7) PoE/PoE+ (Pins 1, 2+; 3, 6-)
Total non-blocking throughput	8 Gbps
Switching capacity	16 Gbps
Forwarding rate	11.904 Mpps
Power method	(1) 54V, 1.1A power adapter (Included) PoE++ (Pins 1, 2+; 3, 6- and 4, 5+; 7, 8-)
Power supply	54V, external, 1.1A/60W
Supported voltage range	44—57V DC
Max. power consumption	9W with PoE input (Excluding PoE output) 8W with AC adapter input (Excluding PoE output)
Total available PoE	PoE++ input: 42W PoE+ input: 16W 60W PoE adapter input: 42W 60W AC adapter input: 52W 210W AC adapter input: 202W* *At 45° C (113° F) operating temperature. Reduced to 161W (230V) or 121W (115V) at 60° C (140° F)
Max. PoE+ wattage per port by PSE	30W
Button	Factory reset
Ambient operating temperature	PoE++ input: -30 to 60° C (-22 to 140° F) 60W AC adapter input: -20 to 45° C (-4 to 113° F) 210W AC adapter input: -20 to 60° C (-4 to 140° F)
Ambient operating humidity	10 to 90% noncondensing
Certifications	CE, FCC, IC

Switching Features

Layer 2 features	STP / RSTP with priorities and port-level disable Port isolation Storm control Port mirroring
-------------------------	--

Multicast / broadcast rate limiting
Flow control
Jumbo frames
Egress rate limit

Layer 3 features

-

LEDs

System

Status

Ethernet

PoE
Link/activity

Application Requirements

UniFI Network

Version 8.0.7 and later